


FW-1WTX

Ultralink 1-Watt Video Transmitter



Chrome-Coat Indoor Housing



Board-Level Transmitter Module



Powder-Coat Indoor Housing



Transmitter in Outdoor NEMA4 Housing

FirstWitness
video surveillance systems

Old Town Hall Building,
Route 11 South
P.O. Box 327
Mt Sidney, Virginia 24467

p. 800.880.1521
540.248.0355
f. 540.248.0920
sales@firstwitness.com

www.firstwitness.com

Specifications for the UltraLink 1 Watt Video Transmitter

High Power Transmitter

RF Output Range	1 Watt
Channel Frequency	2463 MHz
Frequency Stability	+/- 250 KHz, PLL Freq Synthesizer
Power	12 Volt D/C; 120 Volt A/C operation
Video Input	NTSC or PAL 1Vpp, BNC Input Standard 75 Ohms
Operation Temp	-30°C to 60°C
Dimensions	4"wide x 4" high x 4" deep
Antenna	6db built-in directional antenna
FCC ID Number	NH5-FXTX1W

Receiver

RF Input	2411-2483 MHz (4 channel standard)
Frequency Stability	+/- 250 KHz, PLL Freq Synthesizer
Current Draw	135 mA, max
Video Output	NTSC or PAL 1Vpp, BNC Input Standard 75 Ohms
Operation Temp	-30C to 60C
Dimensions	6"wide x 6" high x 4" deep
Antenna	6db built-in
FCC ID Number	Tested under Part 15

FirstWitness
video surveillance systems

Old Town Hall Building,
Route 11 South
P.O. Box 327
Mt Sidney, Virginia 24467

p. 800.880.1521
540.248.0355
f. 540.248.0920
sales@firstwitness.com

www.firstwitness.com