

Wireless G2K Transmitter



The Wireless G2K Transmitter uses our FCC accepted Part 90 transmitter and receiver in specialty camouflaged weatherproof containers. This unit is specifically designed to be used with all Guardian 2000 surveillance systems. Once an alarm is received, the acquired video image is sent to the receiver and the Guardian 2000 video recorder accurately memorializes the captured images. This is the perfect solution where longer range, equipment concealment, and mission success are paramount.

- RF Output: 100mW board level with 250 mW apparent through antenna gain
- Completely weatherproof
- Dimensions: 6" x 6" x 4"
- Channel frequency: 2450~2483 MHz
- Frequency stability: +/- 250 KHz PLL freq. synthesizer
- Video Deviation: 6.3 MHz p.p
- Video Input: NTSC 1Vpp; any Guardian 2000 cameras
- Voltage: 12V (8 size "D") batteries
- User adjusted transmit time
- Operating temp: -30C ~ 50C
- FCC ID# NH5FWVTXBD12A

FirstWitness
video surveillance systems

Old Town Hall Building
Route 11 South
P.O. Box 327
Mt Sidney, Virginia 24467

p. 800.880.1521
540.248.0355
f. 540.248.0920
sales@firstwitness.com

www.firstwitness.com